

# **Quality Control Certificate**

Product: Alumina Column

Product No.: 15433 **Lot No.: 718777** 

Storage Recommendations: Store the column at room temperature below 25°C

Description: The Alumina Column is part of a 3-column setup used for the sample preparation of

environmental-, food- / feed- and similar matrices with DEXTech systems from

LCTech for the analysis of polychlorinated dibenzo-p-dioxins (PCDD), polychlorinated dibenzofurans (PCDF) and polychlorinated biphenyl (PCB)

congeners.

### **Quality Control Release Inspection and Test Specification**

Test Procedure: A solvent blank, spiked with quantification standard has been cleaned on a

DEXTech Plus system, spiked with recovery standard, evaporated with the D-EVA and has been quantified with a HRGC/HRMS DFS from Thermo Fisher Scientific at a

resolution of R > 10000.

Results Blank Value: PCDD/F-TEQ: 0,1 pg/column

(crit: < 0,7 pg/column)

dl-PCB-TEQ: 0,0144 pg/column

(crit: < 0,05 pg/column)

Sum Total PCB: 2,7 pg/column

(crit: < 300 pg/column)

Results Recoveries: PCDD/F 90 to 117 % (crit: 70 to 120 %)

PCB 99 to 116 % (crit: 70 to 120 %)

This is to certify that the Alumina Column, Lot 718777, passed the required test specifications and is released for sale.

date: 26.09.2023 sign.:

The company LCTech GmbH is certified according to ISO 9001





#### QC-Certificate - 15433 - 718777

Hazards: NOT FOR HUMAN OR DRUG USE!

The Alumina Column is designed and prepared for usage with the Universal/standard & Smart Column and Carbon Column from LCTech and for laboratory use only. This product should only be used by qualified personnel familiar with its potential hazards and trained in the handling of hazardous chemicals. Due care should be exercised to prevent unnecessary human contact or ingestion, all procedures should be carried out with suitable gloves, eye protection, and clothing should be worn at all times. Waste should be disposed according to national and

regional regulations.

Quality Control: All ingredients are traceable to certified lots of our supplier. In addition, any

ingredient with a new lot will be checked on contamination and efficiency before releasing for production. Monitoring the ongoing production, several columns are chosen at random day for analysis to check on contamination

and efficiency.

Quality Management: This product was produced using a Quality Management System registered to the

ISO 9001:2015 (DEKRA)

Documentation / table 1 & 2: blankvalues of PCDD/F and PCB
Data Attached: table 3 & 4: 13C-Recoveries of PCDD/F and PCB

Analytics This is to certify that the Alumina Column, Lot , passed the required test

specifications and is released for sale.

Remarks n/a





## QC-Certificate - 15433 - 718777

#### Results:

Lockmass check: No significant disturbances, or indicators for contaminations are detected.

Blanks: n= 6

Table 1: PCDD/F blank

	_	[pg/column]
	2,3,7,8-TCDF	<dl< td=""></dl<>
	1,2,3,7,8-PeCDF	<dl< td=""></dl<>
	2,3,4,7,8-PeCDF	<0,081
[uu	1,2,3,4,7,8-HxCDF	0,033
ďΠ	1,2,3,6,7,8-HxCDF	0,032
g/colun	2,3,4,6,7,8-HxCDF	<0,045
) g	1,2,3,7,8,9-HxCDF	<0,045
으	1,2,3,4,6,7,8-HpCDF	0,1
E I	1,2,3,4,7,8,9-HpCDF	0,101
00	1,2,3,4,6,7,8,9-OCDF	0,11
sample amount	2,3,7,8-TCDD	<0,036
ole ole	1,2,3,7,8-PeCDD	<dl< td=""></dl<>
Ē	1,2,3,4,7,8-HxCDD	0,051
SS	1,2,3,6,7,8-HxCDD	0,13
	1,2,3,7,8,9-HxCDD	0,033
	1,2,3,4,6,7,8-HpCDD	0,15
	1,2,3,4,6,7,8,9-OCDD	0,7

PCDD/F TEQ (2005)	[pg/column]	
lower bound		0,07
upper bound		0,1

Table 2: PCB blank

		[pg/column]
	PCB-#28	0,79
	PCB-#52	0,54
	PCB-#101	0,49
	PCB-#153	0,26
<u>[e</u>	PCB-#138	0,17
amount [pg/sample]	PCB-#180	0,453
/sa	PCB-#81	0,22
pg	PCB-#77	0,2417
Ħ	PCB-#126	0,07
on	PCB-#169	0,242
au	PCB-#123	<0,18
	PCB-#118	0,3
sample	PCB-#114	<0,045
sa	PCB-#105	0,1
	PCB-#167	0,096
	PCB-#156	0,312
	PCB-#157	0,08
	PCB-#189	0,468

PCB-TEQ	[pg/column]
lower bound	0,0144
upper bound	0,0144
Sum DIN	2,7
	_





## QC-Certificate - 15433 - 718777

Table 3: PCDD/F recoveries

		[%]	RSD [%]
	2,3,7,8-TCDF	101	3
	1,2,3,7,8-PeCDF	90	9
	2,3,4,7,8-PeCDF	93	16
[%	1,2,3,4,7,8-HxCDF	114	7
S	1,2,3,6,7,8-HxCDF	117	3
Ţ.	2,3,4,6,7,8-HxCDF	112	7
PCDD/F 13C Recoveries [%]	1,2,3,7,8,9-HxCDF	109	4
် ပို	1,2,3,4,6,7,8-HpCDF	113	4
æ	1,2,3,4,7,8,9-HpCDF	106	9
ဒ္ဓင	1,2,3,4,6,7,8,9-OCDF	105	6
<del>-</del>	2,3,7,8-TCDD	95	8
5	1,2,3,7,8-PeCDD	92	8
8	1,2,3,4,7,8-HxCDD	113	4
٩	1,2,3,6,7,8-HxCDD	97	4
	1,2,3,7,8,9-HxCDD	114	3
	1,2,3,4,6,7,8-HpCDD	105	4
	1,2,3,4,6,7,8,9-OCDD	99	3

Table 4: PCB recoveries

		[%]	RSD [%]
	PCB-#28	99	5
	PCB-#52	101	6
	PCB-#101	103	2
	PCB-#153	100	4
5	PCB-#138	101	3
<u>0</u>	PCB-#180	112	4
ies	PCB-#81	116	0
Ve.	PCB-#77	116	0
Ó	PCB-#126	114	0
R	PCB-#169	116	0
သ္ထ	PCB-#123	104	4
PCB 13C Recoveries [%]	PCB-#118	104	3
	PCB-#114	104	4
	PCB-#105	105	5
	PCB-#167	105	1
	PCB-#156	108	2
	PCB-#157	112	2
	PCB-#189	111	2

